

Neelnox

10752 Deerwood Park Blvd S, Waterview II, Ste#100
Jacksonville, Florida 32256 Tel: 904 880 5557 Fax: 904 302 7757
Email: info@neelnoxmosaics.com Web: www.neelnoxmosaics.com

Y I S H E L F : SERIES 100 INSTALLATION INSTRUCTIONS

Product Features

- Equipped with SoundDefy™ noise concealing technology
- Premium 304 Grade Stainless Steel
- Sloped Bottom*
- Hand Crafted
- PlankScrews™ included for a complete installation

Tools You'll Need



Congratulations On Your Purchase

“Quality is
not an act,
it is a habit.”
-Aristotle

Congratulations on purchasing the finest. Quality has been a habit at Neelnox since the very first day of its inception in 1963 and it is a habit that has strengthened with time. We hope that you are completely satisfied with your new product. Prior to installation please take a few moments to review the guidelines listed here. Should you have any questions or concerns, or if you'd like to share just how happy you are with the product, please feel free to contact us at info@neelnoxmosaics.com.

Installation

- Determine the location where you would like to install the Series 100 Y I SHELF™. Ensure that there are studs in the wall where you would like to install the shelf.
- Place the shelf at the desired location on the substrate and mark along the outer edges of the shelf. Mark an additional horizontal line along the center of the top and bottom of the existing horizontal markings. Now, make additional marks perpendicular to this line at locations of the center of the stud.
- Drill a 5/16" diameter hole on these marks. Install the PlankScrew™ along the marks. Please note that the drill size is slightly smaller than the diameter of the PlankScrew™ in order to for the PlankScrew™ to install in the correct manner by creating it's pitch in the 2x4 stud. A light torque (use manual pressure, a machine is not recommended) will be required to install the PlankScrew™. Tighten the PlankScrew™ till the line pre-marked line on the PlankScrew™. Do not tighten the PlankScrew™ beyond this.
- Ensure that the PlankScrew™ is installed with the 1/16" step facing the top.
- Prepare the included Y I BOND™ by mixing the resin and hardener in equal parts.
- Spread the prepared Y I BOND™ resin and hardener along the top face of the PlankScrew(s)™
- Slide in the Series 100 Y I SHELF™ over the PlankScrew(s)™. Place a weight (approx. 7 lbs) over each PlankScrew(s)™ and secure the Series 100 Y I SHELF™ to the wall with tape.
- Remove weights and tape after a period of 8 hours. The Y I BOND™ cures fully after a period of 24 hours.

Care & Maintenance

- Neelnox recommends 3M Stainless steel cleaners or a damp soft cloth, mild dishwashing soap and a non abrasive sponge if required. Always clean along the direction of the grain. Do not use acid or corrosive solutions, chloride solutions, abrasive pads or steel wool for cleaning.